



NARDI








IMPLEMENTS
FOR PROFESSIONAL
FARMING



NFR

 Mounted cultivator



Mod.								
	HP	KW	Cm	n°	Cm	Cm	Kg	Kg
NFR 5	40-60	30-44	35	5	70	150-180	430	300
NFR 7	60-80	44-59	35	7	70	200	530	380
NFR 9	90-100	67-74	35	9	70	250	620	470
NFR 11	110-140	82-103	35	11	70	300	735	555
NFR 13	140-160	103-120	35	13	70	350	835	630
NFR 15	180-200	132-147	35	15	70	400	950	690

STANDARD FEATURES

- ✓ Shanks with sheared safety bolt made of high-strength tempered steel
- ✓ **NFR 7-9-11** 2° Cat. 3 point hitch
- ✓ **NFR 13-15** 2° e 3°N Cat. 3 point hitch

MAIN TECHNICAL FEATURES



Share made from special heat-treated materials



Strong and sturdy structure



Chain-driven roller and incidence regulation



Heat-treated steel shank and safety bolt

OUR STRENGTHS

- ✓ Structure composed by certified quality materials
- ✓ Share made from special heat-treated materials
- ✓ Shanks made of heat-treated microalloyed material
- ✓ Shanks with safety bolts
- ✓ Traction roller with incidence regulation

YOUR ADVANTAGES

- ✓ High reliability
- ✓ High durability
- ✓ High resistance
- ✓ Protects the structure from impact with obstacles and allows a rapid replacement
- ✓ Allows you to sharpen the ground more of traditional rollers

I dati di peso e di lavoro contenuti nella presente illustrazione s'intendono forniti a semplice titolo indicativo e non impegnativo. The weight and working data contained in the present leaflet are supplied for information only and are not binding

Les descriptions et illustrations de cette notice sont données à titre indicatif et sans engagement



ASSOCIATI:



NARDI S.p.A
Via del Lavoro 24/26
06016 Selci Lama (PG) Italy
tel. +39 075 8610611
fax +39 075 8583446
e-mail: info@grupponardi.it
www.grupponardi.it